



US007360965B2

(12) **United States Patent**
Coscarella

(10) **Patent No.:** **US 7,360,965 B2**
(45) **Date of Patent:** **Apr. 22, 2008**

(54) **CLEANOUT WITH DRAINAGE CAPABILITIES**

(76) Inventor: **Gabe Coscarella**, 15703-64 Street, Edmonton, Alberta (CA) T5Y 2N5

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 742 days.

(21) Appl. No.: **10/691,463**

(22) Filed: **Oct. 21, 2003**

(65) **Prior Publication Data**

US 2005/0072080 A1 Apr. 7, 2005

(30) **Foreign Application Priority Data**

Oct. 21, 2002 (CA) 2409056

(51) **Int. Cl.**
E02B 11/00 (2006.01)

(52) **U.S. Cl.** **405/40**

(58) **Field of Classification Search** 405/39,
405/41, 42; 52/107; 251/120-121, 205,
251/340

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 214,894 A * 4/1879 Draper 405/42
- 540,297 A 6/1895 Brintnall
- 1,109,740 A 9/1914 Dehn
- 1,731,617 A * 10/1929 Fleming 210/165
- 2,898,129 A 8/1959 Sisk

- 3,469,698 A * 9/1969 Blendermann 210/163
- 3,638,431 A * 2/1972 Shelander 405/53
- 3,774,765 A 11/1973 Kane et al.
- 3,973,407 A 8/1976 Vecchio
- 5,431,815 A * 7/1995 Te-Shin 210/459
- 5,970,664 A * 10/1999 Janesky 52/107

FOREIGN PATENT DOCUMENTS

CA 1010743 5/1977

* cited by examiner

Primary Examiner—John Kreck

(74) Attorney, Agent, or Firm—Christensen O'Connor Johnson Kindness PLLC

(57) **ABSTRACT**

A cleanout with adjustable subsurface drainage capabilities which includes a first body and a second body. The first body has a first sidewall and a top access opening. The first sidewall has a plurality of circumferentially spaced and axially oriented first slots. A removable liquid impervious closure closes the top access opening. The second body has a second sidewall and a bottom access opening. The second sidewall has a plurality of circumferentially spaced and axially oriented second slots. The first body and the second body are rotatably engaged with the first sidewall and the second sidewall overlapping. A slot open flow area is provided where the first slots and the second slots overlap. Relative rotation of the first body and the second body alters the relative circumferential spacing of the first slots and the second slots placing them either out of register, partially in register or fully in register and thereby altering the width of the slot open flow area.

5 Claims, 8 Drawing Sheets

