



US007686008B2

(12) **United States Patent**
Willett

(10) **Patent No.:** **US 7,686,008 B2**
(45) **Date of Patent:** **Mar. 30, 2010**

(54) **INSULATION FOR BAKING CHAMBERS IN A MULTI-DECK BAKING OVEN**

(75) Inventor: **Paul Eaton Willett**, Whiteside (AU)

(73) Assignee: **Moffat Pty Limited**, Mulgrave (AU)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 134 days.

(21) Appl. No.: **11/852,754**

(22) Filed: **Sep. 10, 2007**

(65) **Prior Publication Data**

US 2008/0216811 A1 Sep. 11, 2008

(30) **Foreign Application Priority Data**

Sep. 11, 2006 (AU) 2006905005

(51) **Int. Cl.**
F24C 15/16 (2006.01)

(52) **U.S. Cl.** **126/19 R**; 126/21 A; 126/21 R;
99/443 R; 99/447; 99/448

(58) **Field of Classification Search** 126/19 R,
126/21 A, 21 R
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,560,847 A * 11/1925 Parke 126/339
1,980,307 A * 11/1934 Wilkinson et al. 126/39 C
2,077,687 A * 4/1937 Goldbert et al. 219/400

3,362,081 A * 1/1968 Bogenberger 34/467
3,408,785 A * 11/1968 Kochanowski 126/200
4,008,996 A * 2/1977 Wells 432/128
4,253,286 A * 3/1981 Katona 52/171.1
4,527,538 A * 7/1985 Caferro 126/21 R
4,538,050 A * 8/1985 Willett 219/388
4,884,552 A * 12/1989 Wells et al. 126/19 R
5,255,969 A * 10/1993 Cox et al. 312/236
5,277,105 A * 1/1994 Bruno et al. 99/443 C
5,421,320 A * 6/1995 Brown 126/299 R
5,763,857 A * 6/1998 Klement et al. 219/407
5,875,705 A * 3/1999 Knost 99/443 C
6,905,332 B1 * 6/2005 Neal et al. 432/247
7,129,447 B1 * 10/2006 Kim et al. 219/394
2005/0133016 A1 * 6/2005 Neal et al. 126/19 R
2006/0070614 A1 * 4/2006 Spangrud 126/25 R
2007/0266740 A9 * 11/2007 Kendall et al. 68/3 R

FOREIGN PATENT DOCUMENTS

GB 901723 A 7/1962

* cited by examiner

Primary Examiner—Kenneth B Rinehart

Assistant Examiner—Frances Kamps

(74) *Attorney, Agent, or Firm*—Christensen O'Connor Johnson Kindness PLLC

(57) **ABSTRACT**

A multi-deck baking oven including a housing and at least two baking chambers located within the housing, adjacent baking chambers being separated by an insulating layer, at least one of the insulating layers including a hollow partition, wherein each insulating layer dampens the rate of heat flow between the adjacent baking chambers.

16 Claims, 2 Drawing Sheets

