



US007699172B2

(12) **United States Patent**
McTavish et al.

(10) **Patent No.:** **US 7,699,172 B2**
(45) **Date of Patent:** **Apr. 20, 2010**

- (54) **STACKING DELIVERY TRAY**
- (75) Inventors: **Gordon McTavish**, Edmonton (CA); **Cory Koski**, Edmonton (CA); **Hongqiao Li**, Edmonton (CA)
- (73) Assignee: **Drader Manufacturing Industries Ltd.**, Edmonton (CA)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 211 days.

- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- 3,387,740 A 6/1968 Bockenstette
- 3,675,815 A 7/1972 Rehrig
- 3,780,905 A 12/1973 Heroizer
- 4,000,817 A 1/1977 Sanders
- 5,035,326 A 7/1991 Stahl
- 5,287,966 A 2/1994 Stahl
- 5,881,902 A 3/1999 Ackermann
- 6,273,259 B1 8/2001 Stahl
- 6,394,274 B1 5/2002 Cheeseman
- 2004/0060844 A1 4/2004 Stahl

- (21) Appl. No.: **11/817,142**
- (22) PCT Filed: **Feb. 22, 2006**
- (86) PCT No.: **PCT/CA2006/000249**
- § 371 (c)(1), (2), (4) Date: **Aug. 24, 2007**
- (87) PCT Pub. No.: **WO2006/089407**
- PCT Pub. Date: **Aug. 31, 2006**

- FOREIGN PATENT DOCUMENTS
- CA 2276863 12/2005
- Primary Examiner*—Anthony Stashick
- Assistant Examiner*—Harry A Grosso
- (74) *Attorney, Agent, or Firm*—Christensen O'Connor Johnson Kindness PLLC

- (65) **Prior Publication Data**
- US 2008/0110790 A1 May 15, 2008
- (30) **Foreign Application Priority Data**
- Feb. 24, 2005 (CA) 2498571
- (51) **Int. Cl.**
- B65D 21/032** (2006.01)
- B65D 85/62** (2006.01)
- (52) **U.S. Cl.** **206/511; 206/509**
- (58) **Field of Classification Search** **206/505, 206/509, 511, 512, 518**
- See application file for complete search history.

- (57) **ABSTRACT**
- A two position stacking delivery tray is provided which is capable of stacking with itself, and also stacking with existing single position stacking delivery trays. A single uneven upstanding tongue is positioned along a top edge of each of a first side wall and a second side wall. The uneven upstanding tongue defines a first engagement with peaks and valleys. Tongue receivers are positioned in the bottom defining an uneven groove adapted to mate with a single upstanding tongue of an underlying tray having a single stacking product height position. The uneven groove defines a second engagement with peaks and valleys. The peaks and valleys of the first engagement and the second engagement are asymmetrically positioned, so as to provide two stacking product height positions by relative rotation of stacking trays by 180 degrees.

8 Claims, 8 Drawing Sheets

